


HAZE METER



7in color touch screen



Spectral display



Built-in integrating sphere



PC software extension



YH1102

YH1102 haze meter (dual caliber) can easily implement ASTM D1003 non-compensation method, full light transmittance, and haze test.

The open sample chamber can be tested vertically and horizontally, which is suitable for more samples to be tested. YH1102 haze meter adopts PD array detector to meet CIE $V(\lambda)$ 2 degree visual response. Compensation method measurement can achieve high-precision and repeatable light transmittance and haze data measurement.

SHENZHEN THREEENH TECHNOLOGY CO., LTD.

PRODUCT FEATURES

Advantages of haze meter

1

ISO&ASTM

Meet a variety of test requirements, Standards compliant: ASTM D1003/1044, ISO 14782, GB/T 2410, JJF 1303-2011, CIE 15.2, JIS K7105, JIS K7361, JIS K7136

2

Simple operation and quick measurement

The YH1102 haze meter is equipped with a large-size touch screen for easy operation. With a PD array detector, CIE $V(\lambda)^2$ degree visual response enables high precision and repeatable transmittance and fog measurements. USB data output device for docking with laboratory system.

3

Dynamic measurement

Independent light source detector and temperature sensor, constantly monitor light source and environmental change, ensure the reliability of test data.

4

Support a variety of samples

Independent light source detector and temperature sensor, constantly monitor light source and environmental change, ensure the reliability of test data.

5

Support a variety of samples

It provides powerful software for measuring and analyzing fog and light transmittance, which is suitable for quality monitoring and tabulated management of fog and light transmittance data in various industries. The management of users will be digitized at the PC end, the difference of fog and light transmittance will be compared, and the test report form will be generated to facilitate customer customization and management.

Application industry

The YH1102 haze meter is widely used in glass processing, plastic processing, film, display processing, packaging industry, liquid chemical analysis, etc.



Transparent plastic processing



Packaging processing



Glass processing



Laboratory analysis



Film processing



Liquid analysis

Model: YH1102

Optical Geometry: Transmission: 0/D (parallel light illumination, diffuse reflection reception)

Standards compliant: ASTM D1003/1044,ISO 13468,ISO 14782,GB/T 2410,JJF 1303-2011,CIE 15.2,JIS K7105,JIS K7361,JIS K7136

Integrating Sphere Size: Φ 154mm

Illuminant: 400-700nm LED light source

Spectrophotometric Mode: /

Sensor: PD array detector, meeting CIE V(λ) 2 degree visual response

Wavelength Range: /

Wavelength Pitch: /

Semiband Width: /

Transmittance range: 0-100%

Measuring Aperture: Φ 20mm/ Φ 8mm double caliber

Sample size: The thickness is less than 170mm

Color Space: /

Color Difference Formula: /

Other Colorimetric Data: Haze (ASTM D1003/1044, ISO 13468), transmittance T (ASTM)

Observer Angle: 2°

Illuminants: D65,A,C

Displayed Data: Pass/fail result

Measuring Time: about 1.5s

Precision: 0.01

Repeatability: Φ 20mm Caliber,< 0.05

(After the instrument is warmed up and corrected, the standard deviation value of the standard haze sheet with a haze of about 30 is tested at an interval of 5s)

Inter-instrument Error: Φ 20mm Caliber,< 0.4

(After the instrument is warmed up and corrected, test the standard deviation of the haze standard haze sheet and the reference value at an interval of 5s)

Size: Length X Width X Height=290X211X511mm

Weight: About 7.6 kg

Power Supply: DC 24V, 3A Power Adapter

Light Source Device Life: 5 years, more than 3 million times measurements.

Display: 7" TFT Capacitive Screen-touch Display

Data Port: USB & Print serial port

Data Storage: Standard 1000 Pcs, Sample 20000 Pcs

Language: Simplified Chinese, Traditional Chinese, English

Working Environment: Temperature: 0~40°C; Humidity: 0~85% (No Condensation)

Storage Environment: Temperature: -20~50°C; Humidity: 0~85% (No Condensation)

Standard Accessory: Power adapter, manual, quality management software (download from official website), data cable, 0% calibration box, measuring caliber

Optional Accessory: Micro printer, test fixture, standard haze film, foot switch

Notes: The specifications are subject to change without notice.

SHENZHEN THREENH TECHNOLOGY CO., LTD.



Spectrophotometers



Colorimeters



Haze Meters



Gloss Meters



Test Charts





Light Booths

★ CONTACT US

 web:www.3nh.com

 Email: 3nh@3nh.com

 Tel:0086-755-26508999

 Fax: 86-0755-27190609

 Address:F/6, Block 5B, Skyworth Inno Valley, Tangtou 1st Road,
Shiyan, Baoan District, Shenzhen, P.R. China