


# Accurate measurement of sample reflectance and various chromaticity data





## YS4510Plus-Spectrophotometer


YS4510Plus-Spectrophotometer with 45/0 geometrical optics structure (45 ring-shaped illumination, vertical viewing), comply with CIE No.15. Adopting concave grating light splitting method, accurately measure the reflectivity and various chromaticity data of samples. users can customize the measurement aperture ( $\Phi 8 / \Phi 4 / \Phi 2\text{mm}$ ) according to the sample measuring demands, meet the industry accurate color measurement and quality control.



- 

Concave-Grating Spectral
- 

Long life LED light sources
- 

Customized measuring aperture
- 

High-configuration electronic hardware


## PRODUCT FEATURES

1. Perfect combination of beautiful appearance and the human body mechanics structural design
2. 45/0 geometrical optics, conforms with CIE No.15, GB/T 3978, GB 2893, GB/T 18833, ISO7724/1, ASTM E1164, DIN5033 Teil7
3. Accurate color measurement and quality control
4. High electronic hardware configuration: 3.5-inch TFT color LCD, Capacitive Touch Screen, concave grating, 256 Image Element Double Arrays CMOS Image Sensor
5. Measure sample spectra, accurate Lab data, can be used in color matching and accurate color transmission
6. Use long life and low power consumption combined LED light source
7. Customized single aperture: MAV: >8mm/φ10mm; SAV: φ4mm/φ5mm; SSAV: φ2mm/φ3mm, suitable for more samples
8. USB port, widely useful
9. PC software has a powerful function extension




## APPLICATION INDUSTRIES


The grating spectrophotometer can easily achieve the accurate transmission of color, and can also be used as the detection equipment of the accurate color matching system; it is used for accurate color measurement and quality control of traffic road signs, plastics, electronics, paint and ink, textile and garment, printing and dyeing, ceramics and other industries.



Traffic road sign



Textile



Plastic




Paint



Food



Laboratory



Other

## SPECIFICATION PARAMETERS

**Model:** YS4510PLUS

**Illumination:** 45/0 (45 circular illumination, vertical viewing)

**Standard:** CIE No.15, GB/T3978, GB2893, GB/T 18833, ISO7724-1, ASTM E1164, DIN5033 Teil7

**Integrating Sphere Size:** 48mm

**Light Source:** Combined LED Light

**Spectrophotometric Mode:** Concave Grating

**Sensor:** 256 Image Element Double Array CMOS Image Sensor

**Wavelength Range:** 400-700nm

**Wavelength Interval:** 10nm

**Semiband Width:** 10nm

**Measured Reflectance Range:** 0-200%

**Measuring Aperture:** customized single aperture: MAV: φ8mm/φ10mm;

SAV: φ4mm/φ5mm; SSAV: φ2mm/φ3mm

**Color Space:** CIE LAB, XYZ, Yxy, LCh, CIE LUV, Hunter LAB, βxy

**Color Difference Formula:**  $\Delta E^*ab, \Delta E^*uv, \Delta E^*94, \Delta E^*cmc(2:1), \Delta E^*cmc(1:1), \Delta E^*00, \Delta E$  (Hunter)

**Other Colorimetric Index:** WI (ASTM E313, CIE/ISO, AATCC, Hunter), YI (ASTM D1925, ASTM 313), TI (ASTM E313, CIE/ISO), Metamerism Index MI, Staining Fastness, Color Fastness, Color Strength, Opacity

**Illuminant:** D65, A, C, D50, D55, D75, F1, F2 (CWF), F3, F4, F5, F6, F7 (DLF), F8, F9, F10 (TPL5), F11 (TL84), F12 (TL83/U30)

**Displayed Data:** Spectrogram/Values, Samples Chromaticity Values, Color Difference Values/Graph, PASS/FAIL Result, Color Offset

**Observer Angle:** 2°/10°

**Measuring Time:** 1.5s

**Repeatability:** Spectral reflectance: MAV, standard deviation within 0.1% (400~700nm: within 0.2%)

**Chromaticity value:** MAV, within  $\Delta E^*ab$  0.05 (After calibration, measure the average value of the white board 30 times each 5S.)

**Inter-instrument agreement:** MAV, within  $\Delta E^*ab$  0.2 (Average value for 12 BCRA series II color tiles)

**Battery:** Li-ion battery. 5000 measurements within 8 hours

**Dimension:** L\*W\*H=184\*77\*105mm

**Weight:** 600g

**Illuminant Life Span:** 5 years, more than 3 million times measurements

**Display:** 3.5-inch TFT color LCD, Capacitive Touch Screen

**Data Port:** USB

**Data Storage:** Standard 1000 Pcs, Sample 28000 Pcs

**Language:** English, Chinese

**Operating Environment:** 0~40°C, 0~85%RH (no condensing), Altitude < 2000m

**Storage Environment:** -20~50°C, 0~85%RH (no condensing)

**Standard accessories:** power adapter, data line, built-in lithium batteries, instructions, quality control software (download from official website), black and white calibration board, protection cover, polarization filter box (Optional accessories: Micro printer, Powder test box, multi-functional test component)

## GUANGDONG THREENH TECHNOLOGY CO., LTD.



Spectrophotometers



Colorimeters



Haze Meters



Gloss Meters



Test Charts



Light Booths

## ★ CONTACT US

web: [www.3nh.com](http://www.3nh.com)

Email: [3nh@3nh.com](mailto:3nh@3nh.com)

Tel: 0086-020-82880288

Add: 6-8th floors, Building B33, Low Carbon Headquarters Park, Xincheng Road No.400, Zengcheng District, Guangzhou, Guangdong Province, China